C Programs: Simple Statements and Expressions

C Program Structure

A C program that consists of only one function has the following form:

```
preprocessor directives

main function heading
{
  declarations

  statements

}
```

We have already seen some `preprocessor directives` and have discussed some `variable declarations`.

Statements

Statements are instructions to be executed by the computer. C has a number of different types of instructions. In the course we will study most of them.

Today we start with three basic types: function call, assignment and function return.

Function Call

Function call has the following syntax:

```
<functionName>(<arg1>,<arg2>,...,<argN>);
```

Here, `<functionName>` is the name of the function (e.g., `printf`), and `<arg1>`,... `<arg2>` are arguments that the function takes.

C distinguishes between C standard library functions and user-defined functions.

Functions in standard C library. a wide range of tasks in C are not performed by C statements. Instead, these tasks are *outsourced* to a collection of functions that is available for use with *any* C program. This collection is called the standard C library.

These functions have already been implemented by the C developers: all you need to do in order to use them is to provide a preprocessor directive `#include` which would specify the exact part of the standard C library which contains the function(s) you are using.

The following standard C library files contain functions important for our course:

File	Explanation	Examples
`stdio.h`	Standard Input/Output, File Input/Output	`printf()`, `scanf()`
`math.h`	Mathematical functions	`sqrt(), sin(), cos(), log(), exp()`
`stdlib.h`	Memory allocation functions, misc functions	`malloc(), free(), rand(), atoi()`
`string.h`	String manipulation functions	`strcpy(), strcat(), strlen()`
`time.h`	Functions related to time and system time	`clock(), localtime(), difftime()`

(note, other components of standard C library exist, but they will not be covered in the course).

To specify that the included file belongs to the standard C library put the file name in angle brackets (<>) in the `#include` command:

```
#include <stdio.h>
#include <math.h>
#include <stdlib.h>
#include <string.h>
#include <time.h>
```

User-defined functions. User-defined functions are reusable program components that the programmer elected to make structurally independent from the main program. Each user-defined function must have a name, a type and a list of input parameters (if any). The programmer is responsible for providing proper definition and (if necessary) declaration of the function.

More on this - in two weeks!

List of standard library functions. You have already seen two I/O functions: `printf()` and `scanf()`. The list below highlights some of the mathematical functions available to you in C. See Appendix B. of the textbook for full list.

Function declaration	Library header file	Purpose	Example
`int abs(int)`	`stdlib.h`	absolute value	`abs(-4)` = 4
`double fabs(double)`	`math.h`	`abs()` for floating point values	`fabs(-3.432)`=3.432
`double ceil(double)`	`math.h`	smallest integral value	`ceil(7.453)` = 7.0
		no less than argument	`ceil(-4.53)`= -4.0
`double floor(double)`	`math.h`	largest integral value	`floor(-4.56)`=-5.0
		no less than the argument	`floor(6.54)` = 6.0
`double cos(double)`	`math.h`	cosine	`cos(0.0)`=1.0
`double sin(double)`	`math.h`	sine	`sin(0.0)` = 0.0
`double tan(double)`	`math.h`	tangent	`tan(0.0)` = 0.0
`double exp(double)`	`math.h`	e^x (x is argument)	`exp(1.0)`=2.71828...
`double log(double)`	`math.h`	natural logarithm	`log(exp(1.0))`= 1.0
`double log10(double)`	`math.h`	base-10 logarithm	`log10(1000.0)`= 3.0
`double pow(double, double)`	`math.h`	power	`pow(2.0,4.0)` = 16.0
`double sqrt(double)`	`math.h`	square root	`sqrt(9.0)`=3.0
`int rand(void)`	`stdlib.h`	pseudorandom number generator	`rand()`
`void srand(unsigned int)`	`stdlib.h`	reset random number generator	`srand(100)`

int main(). One user-defined C function, `main()` has special meaning in C. This function represents the main body of the C program. As such, when the

executable file of the C program is loaded into main memory to be run by the CPU, the execution of the program starts at the beginning of the `main()` function.

In ANSI standard `main()` **must** have return type `int` and `must have no` input parameters. The type of the function **must** be explicitly declared in ANSI C (modern dialects of C do not require it, though).

Function Return Statment

Syntax. Function return statment has the following syntax:

```
return <Expression>;
```

Here, `<Expression>` is a C expression (see below).

Note, ANSI C standard requires a `return` statement to be the last executed statement of any function (including `main()`).

As such, it is a good practice to put a `return` statement at the end of each function *as soon as the function is created*.

For example, start your `main()` functions with the following stub:

```
/*  Comment goes here */
int main() {

   return 0;
}
```

Semantics. When `return` statement is encountered during the run of the program, the following actions are performed:

1. Expression `<Expression>` gets evaluated.
2. Curent function terminates its operation.
3. The computed value is returned to the caller function.
4. If current function is `main()`, the program terminates its work.

Type match. The key rule to remember is that the value of the expression in the `return` statement must have the same type as the declared type of the function.

For example, `main()` is always declared as `int main()`. Therefore, the following code:

```
/*  Comment goes here */
int main() {

   return 1.234;
}
```

will result in a compiler error.

Assignment

Assignment statements are the building blocks of the C program. Assignment statements allow variables to receive new values as a result of various computations performed within a program.

Syntax. The assignment statements we will be studying for now have the following syntax:

```
<VariableName> = <Expression>;
```

Here, `<VariableName>` is a name of a program variable and `<Expression>` is a C expression (see below).

Semantics. The assignment statement is evaluated as follows:

1. `<Expression>` is evaluated.
2. Computed value of `<Expression>` is stored in the memory cells allocated for the variable `<VariableName>`.

Example.

```
int x, y;
float a,b;

x = 0;
y = x + 1;
x = x + x;
a = 2.0;
b = a / (y + x);
```

Constraints. The evaluation of the assignment statement is subject to the following conditions:

1. **Declared variable.** Varibable `<VariableName>` must be declared prior to its use in the assignment statement.
2. **Type match.** `<Expression>` must evaluate to a type compatible with the declared type for the variable `<VariableName>`.

Expressions

At this point we concentrate on arithmetic expressions. The three general forms of an expression are

1. `<Operand> <Operation>`
2. `<Operation> <Operand>`
3. `<Operand> <Operation> <Operand>`

C has the following operations:

Operation	Arity	Meaning	Example
`+`	binary	addition	`5 + 6` evaluates to 11
`-`	binary	subtraction	`6 - 5` evaluates to 1
`*`	binary	multiplication	`4 * 3` evaluates to 12
`/`	binary	integer division	`4/5` evaluates to 0
`/`	binary	division	`4.0/5.0` evaluates to 0.8
`%`	binary	remainder	`10 % 7` evaluates to 3
`-`	unary	unary minus	`- 4` evaluates to -4
`+`	unary	unary plus	`+4` evaluates to 4

`<Operand>` can be any of the following:

- constant value (`2, 5.6,` etc.)
- defined constant (`HUNDRED`)
- variable name (`currentStateVote`)
- function call (`log10(x)`)
- (arithmetic) expression in parentheses (`(log10(x) + 5)`)

Evaluation, operation precedence. Arithmetic expressions in C are evaluated according to the mathematical rules. Generally speaking, given an arithmetic expression in C, its evaluation proceeds as follows:

1. Using C operator precedence and associativity rules, the operation `<Op>` with the least precedence (i.e., last to be evaluated) is established.
2. The expression is represented as `<Operand1> <Op> <Operand2>`[1]
3. Operand `<Operand1>` is evaluated.
4. Operand `<Operand2>` is evaluated.
5. The result of the operation `<Op>` applied to the results of evaluating `<Operand1>` and `<Operand2>` is evaluated. This result is returned as the value of the expression.

As seen, expression evaluation depends on operator precedence. The precedence rules are:

Precedence level	Operators
1. (highest)	parentheses
2.	`+,-` (unary)
3.	`*, /, &`
4. (lowest)	`+, -` (binary)

The associativity rule is:

> **Unary operators** in the same subexpression and at the same precedence level are evaluated right-to-left (right-associativity).
>
> **Binary operators** in the same subexpression and at the same precedence level are evaluated left-to-right (left-associativity).

Examples. Expression `a + b*c - (15 + a * n) + 23` has the following precedence of operations: `((a + (b*c)) - (15 + (a*n))) + 23`.

Expression `a + b + -c* -+-d` has the following precedence of operations: `((a+b)+ ((-c) * (-(+(- d))))`.

Expression `b * c / e % f` has the following precedence of operations: `((b*c)/e)% f`.

Type of expression. Type conversion.

- int. If both operands (sub-expressions) in an arithmetic expression evaluate to `int` values, then the expression evaluates to an `int` value.
- double/float. If both operands (sub-expressions) evaluate to `float` (or `double`), the the expression evaluates to a `float` (`double`) value.
- mix. If one sub-expression evaluates to an `int` and the other to a `float` (`double`), then the expression evaluates to a `float` (`double`).

Note. This is how the type of the division operation is determined: if both operands are integers, integer division is applied, otherwise - floating point division.

[1] In case of binary operators. For unary operators, similar intuition holds, except, only one operand gets evaluated.