

## From E-R Models to Relational Databases

### E-R Modeling Framework vs. Relational Database Model

#### Entity-Relationship Models

Entities:	objects
Attributes:	individual features of objects
Keys:	means of unique identification of objects
Relationships:	associations between objects
Entity Sets:	collections of objects
Relationship Sets:	collections of associations
Constraints:	restrictions on objects and associations
Weak Entity Sets:	entity sets w/o a key



#### Relational Database Model

Relational Table:	2D representation of data
Table row:	data about a single object
Table column:	one attribute
Table schema:	list of columns making a table
Database schema:	list of relational table schemas
Primary key:	unique identification of rows in tables
Foreign key:	primary key of one table included in another table

### From E-R Models to Database Schemas

#### Basic Translation

**Entity Sets** are translated into relational tables with the same attributes and the same *primary keys*.

**Note:** This applies only to **strong entity sets**.

**Relationship Sets** are translated into relational tables which consist of the following attributes:

- *Primary keys* of all tables representing entity sets which participate in the relationship set. Must be declared as *foreign keys*.
- Any *identifying attributes* of the relationship set.

**Note:** The *primary key* of the new relational table is application-dependent. The following is possible:

- The primary key of the new table is the *union of all foreign key attributes* in the table.
- The primary key of the new table is the *union of all foreign key attributes* in the table plus *one or more descriptive attributes*.
- The primary key of the new table is a *subset* of the foreign key attributes.

## Representing Different Types of Relationship Sets

The **basic translation** mechanism works for **strong entity sets** and **many-to-many** relationship sets.

Constrained (many-to-one, one-to-one) relationship sets may be translated in several different ways.

### Many-to-one relationship sets:

Suppose we have entity sets  $E$  and  $F$  and a relationship set  $R$  which is many-to-one from  $F$  to  $E$ . This can be translated into relational model in one of the following ways.

1. **Basic translation.** Use basic translation to create relational tables  $E$ ,  $F$  and  $R$  representing the two entity sets and the relationship set respectively. **Do not** include attributes from the primary key of  $E$  into the primary key of  $R$ .
2. **Special translation.** Use basic translation to create relational table  $E$  representing the entity set  $E$ . Create one relational table  $F$  to represent both  $F$  and  $R$  as follows:
  - $F$  contains the following attributes:
    - All attributes of  $F$ .
    - Primary key of  $E$  (declare a foreign key).
    - Any identifying attributes of  $R$ .
  - Primary key of  $F$  is the primary key of  $F$ .

### One-to-one relationship sets:

Suppose we have entity sets  $E$  and  $F$  and a relationship set  $R$  which is one-to-one between  $E$  and  $F$ . This can be translated into relational model in one of the following ways.

1. **Basic translation.** Use basic translation to create relational tables  $E$ ,  $F$  and  $R$  representing the two entity sets and the relationship set respectively. Select the primary key of  $R$  to be EITHER the primary key of  $E$  OR the primary key of  $F$ .
2. **Special translation 1.** Treat  $R$  as a many-to-one relationship set from  $E$  to  $F$  and translate using the special translation for many-to-one relationships.
3. **Special translation 2.** Treat  $R$  as a many-to-one relationship set from  $f$  to  $E$  and translate using the special translation for many-to-one relationships.
4. **Special translation 3.** Combination of **Special translation 1** and **Special translation 2**. In this case, table  $E$  will contain the primary key of  $F$  and table  $F$  will contain the primary key of  $E$ .

## Representing Weak Entity Sets

A **Weak entity set** comes with a many-to-one **identifying relationship**. Let  $F$  be a weak entity set,  $E$  be its identifying owner and  $R$  be the identifying relationship. Then, the relational table for  $F$  is constructed as follows:

- $F$  contains the following attributes:
  - All attributes of  $F$ .
  - Primary key of  $E$  (declare a foreign key).
  - Any identifying attributes of  $R$ .
- The *primary key* of  $F$  consists of the primary key of  $E$  and the discriminator attributes of  $F$ .

**Note:** To create a relational table for a weak entity set, we basically are using the **special translation** for a many-to-one relationship set, with the only change being the designation of the primary key in the new table.

## Representing Aggregation

Let  $R$  be a relationship set and  $G$  be an entity set, and let  $S$  be a relationship set between  $G$  and  $R$ , where  $R$  is treated as an aggregate.

To translate  $G$  into relational data model:

1. Determine the primary key for  $R$ .
2. Follow the **basic translation** or **special translation** rules outlined above. Use the primary key for  $R$  in the translation.

## Representing Class Hierarchies

Class Hierarchies can be converted into relational database schemas in three different ways: **E-R-style**, **Object-Oriented-style** and via a **universal table**.

### E-R-style Conversion

- Each entity set in the class hierarchy is represented as a separate relational table.
- The attributes for each table are: the attributes of the respective entity set and the primary key attributes from the root entity set.
- All relational tables have the same primary key.

### Object-Oriented Conversion

- Each **terminal path** in the class hierarchy is represented as a separate relational table.
- The attributes for each table are the union of attributes in all entity sets located on the terminal path represented by the table.
- The primary key is the primary key of the root entity set.

## Universal Table Conversion

- All entity sets are represented as a single **universal table**
- The attributes of the universal table are the union of all attributes in all entity sets.
- The primary key is the primary key of the root entity set.