From E-R Models to Relational Databases

E-R Modeling Framework vs. Relational Database Model

Entity-Relationship Models			**Relational Database Model**	
Entities:	objects		Relatinal Table:	2D representation of data
Attributes:	individual features of objects		Table row:	data about a single object
Keys:	means of unique identification of objects		Table column:	one attribute
Relationships:	associations between objects	$\Leftrightarrow$	Table schema:	list of columns making a table
Entity Sets:	collections of objects		Database schema:	list of relational table schemas
Relationship Sets:	collections of associations		Primary key:	unique identification of rows in tables
Constraints:	restrictions on objects and associations		Foreign key:	primary key of one table included in another table
Weak Entity Sets:	entity sets w/o a key			

From E-R Models to Database Schemas

Basic Translation

Entity Sets are translated into relational tables with the same attributes and the same *primary keys*.

Note: This applies only to **strong entity sets**.

Relationship Sets are translated into relational tables which consist of the following attributes:

- *Primary keys* of all tables representing entity sets which participate in the relationship set. Must be declared as *foreign keys*.
- Any *identifying attributes* of the relationship set.

Note: The *primary key* of the new relational table is application-dependent. The following is possible:

- The primary key of the new table is the *union of all foreign key attributes* in the table.
- The primary key of the new table is the *union of all foreign key attributes* in the table plus *one or more desciptive attributes.*
- The primary key of the new table is a *subset* of the foreign key attributes.

Representing Different Types of Relationship Sets

The **basic translation** mechanism works for **strong entity sets** and **many-to-many** relationship sets.

Constrained (many-to-one, one-to-one) relationship sets may be translated in several different ways.

Many-to-one relationship sets:

Suppose we have entity sets E and F and a relationship set R which is many-to-one from F to E. This can be translated into relational model in one of the following ways.

1. **Basic translation.** Use basic translation to create relational tables E, F and R representing the two entity sets and the relationship set respectively. **Do not** include attributes from the primary key of E into the primary key of R.
2. **Special translation.** Use basic translation to create relational table E representing the entity set E. Create one relational table F to represent both F and R as follows:
   - F contains the following attrbiutes:
     - All attributes of F.
     - Primary key of E (declare a foreign key).
     - Any identifying attributes of R.
   - Primary key of F is the primary key of F.

One-to-one relationship sets:

Suppose we have entity sets E and F and a relationship set R which is one-to-one between E and F. This can be translated into relational model in one of the following ways.

1. **Basic translation.** Use basic translation to create relational tables E, F and R representing the two entity sets and the relationship set respectively. Select the primary key of R to be EITHER the primary key of E OR the primary key of F.
2. **Special translation 1.** Treat R as a many-to-one relationship set from E to F and translate using the special translation for many-to-one relationships.
3. **Special translation 2.** Treat R as a many-to-one relationship set from f to E and translate using the special translation for many-to-one relationships.
4. **Special translation 3.** Combination of **Special translation 1** and **Special translation 2**. In this case, table E will contain the primary key of F and table **F** will contain the primary key of E.

Representing Weak Entity Sets

A **Weak entity set** comes with a many-to-one **identifying relationship**. Let F be a weak entity set, E be its identifying owner and R be the identifying relationship. Then, the relational table for F is constructed as follows:

- F contains the following attributes:
  - All attributes of F.
  - Primary key of E (declare a foreign key).
  - Any identifying attributes of R.
- The *primary key* of F consists of the primary key of E and the discriminator attributes of F.

Note: To create a relational table for a weak entity set, we basically are using the **special translation** for a many-to-one relationship set, with the only change being the designation of the primary key in the new table.

Representing Aggregation

Let R be a relationship set and G be an entity set, and let S be a relationship set between G and R, where R is treated as a aggregate.

To translate G into relational data model:

1. Determine the primary key for R.
2. Follow the **basic translation** or **special translation** rules outlined above. Use the primary key for R in the translation.

Representing Class Hierarchies

Class Hierachies can be converted into relational database schemas in three different ways: **E-R-syle, Object-Oriented-style** and via a **universal table**.

E-R-style Conversion

- Each entity set in the class hierarchy is represented as a separate relational table.
- The attributes for each table are: the attrbiutes of the respective entity set and the primary key attributes from the root entity set.
- All relational tables have the same primary key.

Object-Oriented Conversion

- Each **terminal path** in the class hierarchy is represented as a separate relational table.
- The attributes for each table are the union of attributes in all entity sets located on the terminal path represented by the table.
- The primary key is the primary key of the root entity set.

Universal Table Conversion

- All entity sets are represented as a sinlge **universal table**
- The attributes of the universal table are the union of all attributes in all entity sets.
- The primary key is the primary key of the root entity set.