Chapter Overview

Introduction CLIPS overview

Notation
similar to regular expressions

Facts
elementary statements

Rules
relations between statements

Variables, Operators, Functions
advanced pattern matching

Input/Output
getting knowledge into and out of CLIPS

Program Execution

User Interface
command line or GUI

Introduction

CLIPS stands for
C Language Implementation Production System

forward-chaining
starting from the facts, a solution is developed

pattern-matching
Rete matching algorithm: find "fitting" rules and facts

knowledge-based system shell
empty tool, to be filled with knowledge

multiparadigm programming language
rule-based, object-oriented (COOL) and procedural

Notation

close to LISP

symbols, characters, keywords
entered exactly as shown: `(example)`

square brackets [...]
contents are optional: `(example [test])`

less than / greater than `< ...>`
replace contents by an instance of that type
`(example <char>)`

star $\star$
replace with zero or more instances of the type `<char>`$\star$

plus `+`
replace with one or more instances of the type `<char>+` (is equivalent to `<char> <char>`$\star$)

vertical bar `|`
choice among a set of items: `true | false`

Tokens and Fields

tokens
groups of characters with special meaning for CLIPS, e.g. `( ) \` separated by delimiters (space, tab, Carriage Return, ...)

fields
particularly important group of tokens
CLIPS primitive data types

- float
  decimal point `1.5` or exponential notation `3.7e10`
- integer
  `[sign] <digit>+`
- symbol
  `<printable ASCII character>+`
  e.g. `this-is-a-symbol, wrzlbrmft, !?@*+`

- string
  delimited by double quotes
  e.g. `"This is a string"`
- external address
  addres of external data structure returned by user-defined functions
- instance name (used with COOL)
  delimited by square brackets
- instance address (used with COOL)
  return values from functions

Enter / Exit

entering CLIPS

double-click on icon, or type program name
system prompt appears:
`CLIPS>`

exiting CLIPS

at the system prompt
`CLIPS>`
type `(exit)`
Note: enclosing parentheses are important; they indicate a command to be executed, not just a symbol

Facts

elementary information item

relation name

symbolic field used to access the information

slots (zero or more)

symbolic fields with associated values

deftemplate construct

used to define the structure of a fact (names and number of slots)

deffacts

used to define initial groups of facts

Examples

of facts

ordered fact

```
(person-name Franz J. Kurfess)
```

deftemplate fact

```
(deftemplate person "deftemplate example"
   (slot name)
   (slot age)
   (slot eye-color)
   (slot haircolor))
```

an instance of a fact is created by

```
(assert (person (name "Franz J. Kurfess")
   (age 40)
   (eye-color brown)
   (haircolor brown)))
```

initial facts

```
(deffacts kurfesses "some members of the K
    (person (name "Franz J. Kurfess") (age
   (eye-color brown) (haircolor brown))
    (person (name "Hubert   Kurfess") (age
   (eye-color blue) (haircolor blond))
    (person (name "Bernhard Kurfess") (age
   (eye-color blue) (haircolor blond))
    (person (name "Heinrich Kurfess") (age
   (eye-color brown) (haircolor blond))
    (person (name "Irmgard  Kurfess") (age
   (eye-color green) (haircolor blond)))
```


Usage

of facts

adding facts

`(assert <fact> +)`

deleting facts

`(retract <fact-index> +)`

modifying facts

`(modify <fact-index> (<slot-name> <slot-value>)+ )`

retracts the original fact and asserts a new, modified fact

duplicating facts

`(duplicate <fact-index> (<slot-name> <slot-value>)+ )`

adds a new, possibly modified fact

inspection of facts

`(facts)`

prints the list of facts

`(watch facts)`

automatically displays changes to the fact list

Rules

components of rules

general format

```
(defrule <rule name> ["comment"]
     <patterns>* ; left-hand side (LHS) or
      =>
      <actions>*) ; right-hand side (RHS)
```

rule header

`defrule` keyword, name of the rule, optional comment string

rule antecedent

patterns to be matched against facts

rule arrow

separates antecedent and consequent

rule consequent

actions to be performed when the rule fires

Examples

of rules

simple rule

```
(defrule birthday-FJK
    (person (name "Franz J. Kurfess")
       (age 40)
       (eye-color brown)
       (haircolor brown))
    (date-today April-13-97)
=>
    (printout t "Happy birthday, Franz!")
    (modify 1 (age 41)))
```

very limited:

- LHS must match facts exactly
- facts must be accessed through their index number
- changes must be stated explicitly

Variables, Operators, Functions

for enhanced pattern matching capabilities

variables

- symbolic name beginning with a question mark "`?`"
- variables in a rule pattern (LHS) are bound to the corresponding values in the fact, and then can be used on the RHS
- all occurrences of a variable in a rule must have the same value
- the first (left-most) occurrence in the LHS determines the value
- bindings are valid only within one rule
- variables can be used to make access to facts more convenient:
  `?age <- (age harry 17)`

wildcards

the question mark "`?`" matches any single field within a fact
the multifield wildcard "`$?`" matches zero or more fields i na fact

field constraints

- `not` constraint " "
  the field can take any value except the one specified
- `or` constraint "`|`"
  specifies alternative values, one of which must match
- `and` constraint "`&`"
  the value of the field must match all specified values
  mostly used to place constraints on the binding of a variable

mathematical operators

basic operators (+,-,*,/) and many functions (trigonometric, logarithmic, exponential) are supported
prefix notation
no built-in precedence, only left-to-right and parentheses

test feature

evaluates an expression in the LHS instead of matching a pattern agains a fact

pattern connectives

multiple patterns in the LHS are implicitly AND-connected
patterns can also be explicitly connected via `and, or, not`

user-defined functions

external functions written in C or other languages can be integrated

Examples

of rules

more complex rule

```
(defrule find-blue-eyes
     (person (name ?name)
       (eye-color blue))
 =>
     (printout t ?name " has blue eyes." C
```


rule with field constraints

```
(defrule silly-eye-hair-match
    (person (name ?name1)
         (eye-color ?eyes1&blue|green)
         (hair-color ?hair1&~black))
    (person (name ?name2&~?name1)
         (eye-color ?eyes2&~eyes1)
         (hair-color ?hair2&red|hair1))
 =>
  (printout t ?name1 " has "?eyes1 " eyes
           ?hair1 " hair." CRLF)
  (printout t ?name2 " has "?eyes2 " eyes
           ?hair2 " hair." CRLF))
```


Manipulation of Constructs

show list of constructs

`(list-defrules)`, `(list-deftemplates)`, `(list-deffacts)` prints a list of the respective constructs

show text of constructs

`(ppdefrule <defrule-name>)`, `(ppdeftemplate <deftemplate-name>)`, `(ppdeffacts <deffacts-name>)` displays the text of the construct ("pretty print")

deleting constructs

`(undefrule <defrule-name>)`, `(undeftemplate <deftemplate-name>)`, `(undeffacts <deffacts-name>)` deletes the construct (if it is not in use)

clearing the CLIPS environment

`(clear)` removes all constructs and adds the initial facts to the CLIPS environment

Input / Output

print information

`(printout <logical-device> <print-items>*)`
logical device frequently is the standard output device `t` (terminal)

terminal input

`(read [<logical-device>])`
`(readline [<logical-device>])`
read an atom or string from a logical device
the logical device can be a file which must be open

open / close file

`(open <file-name> <file-ID> [<mode>])`
`(close [<file-ID>])`
open /close file with `<file-id>` as internal name

load constructs from file

`(load <file-name>)` [1]

save constructs to file

`(save <file-name>)` saves all current constructs to the file

[1] backslash \ is a special character and must be "quoted" (preceded by a backslash \)
e.g. `(load "B:\\clips\\example.clp")`

Program Execution

execution of rules

agenda

if all patterns of a rule match with facts, it is put on the agenda
`(agenda)` displays all activated rules

salience

indicates priority of rules

refraction

rules fire only once for a specific set of facts
`(refresh <rule-name>)` reactivates rules

execution of a program

- `(reset)` prepares (re)start of a program:
  all previous facts are deleted
  initial facts are asserted
  rules matching these facts are put on the agenda
- `(run [<limit>])` starts the execution
- breakpoints
  `(set-break [<rule-name>])` stops the execution before the rule fires,
  continue with `run`
  `(remove-break [<rule-name>])`,
  `(show-breaks)`

Watching

facts, rules, activations, ...

watching the execution

`(watch <watch-item>)` prints messages about activities concerning a `<watch-item>` (*facts, rules, activations, statistics, compilation, focus, all*)
`(unwatch <watch-item>)` turns the messages off

facts

assertions (add) and retractions (delete) of facts

rules

message for each rule that is fired

activations

activated rules: matching antecedents
these rules are on the agenda

statistics
information about the program execution
(number of rules fired, run time, ...)

compilation *default*
constructs loaded by the `(load)` command

focus
used with modules

User Interface

interaction with CLIPS

menu-based version
most relevant commands are available
through windows and menus

Chapter Review

Introduction CLIPS overview

Notation
similar to LISP, regular expressions

Facts
`(deftemplate), (deffacts)`
assert / retract

Rules
`(defrule ...)`, agenda

Variables, Operators, Functions
advanced pattern matching

Input/Output
`(printout ...), (read ...), (load ...)`

Program Execution
`(reset), (run)`, breakpoints

User Interface command line or GUI