Chapter Overview

Rule-Based Reasoning with CLIPS

Introduction
Review Lessons "Rule-Based Reasoning", "CLIPS"

Forward Reasoning
Example: Flood Warning Example: Boxer

Rete Algorithm
Example: Cats and Dogs

Backward Reasoning
Example: Dinner Choices Example: Baseball

Chapter Review

Forward Reasoning

from data towards conclusions

matching known facts are compared with the premises of rules
if all premises of a rule are true, it is satisfied

conflict resolution if multiple rules are satisfied, one must be selected

execution the selected rule is applied
new facts or rules can be generated

usage need for quick response, few facts, few rules many acceptable conclusions

domains monitoring and real-time process control, synthesis; design, configuration, planning, scheduling

Flood Evacuation

example forward reasoning

problem
flood warning and evacuation system for a flood-prone region

problem analysis

- relatively small number of parameters and rules
- relations known prior to execution
- data acquisition automatically from sensors
- continuous monitoring required

design decisions

- forward reasoning
- confidence factors
- inference network

internal representation

- *rules:* rule number, parameters in the premises (upstream elements), parameters in the conclusions (downstream elements), premises, conclusions
- *parameters:* name, rules that modify the parameter, rules using the parameter, values and confidence factor (if known)
- *input data:* list of parameters used as inputs
- *conclusions:* output parameters

BOXER

example forward reasoning

problem

system for arranging things to be packed into boxes

problem analysis

- relatively small number of parameters and rules
- not all relations known prior to execution
- synthesis problem: many possible solutions
- no optimal solution required
- pattern matching required for properties of objects

design decisions

- forward reasoning
- pattern matching system

- conflict resolution
  1) larger number of instantiated premises first
  2) ordering of input data
- grouping of rules, reflects overall packing strategy
- some simplifying assumptions

Pattern Matching

efficiency considerations

problem

pattern matching can be extremely inefficient:
all rules are compared with all the facts in every cycle
rules * facts^{premises}

observation

most of these comparisons are not necessary in each step, only for changes in the fact base

solution

keep a list of satisfied rules
modify it only when changes occur due to addition or deletion of facts

Rete Algorithm

efficient pattern matching

basic idea

keep track of satisfied rules
updates according to changes in the fact base

pattern network

set of trees from all premises of all rules

join network

connects leaf nodes of the trees that share variables
checks consistency of variable bindings

changed facts

modify the corresponding entries in the pattern and join network

Conflict Resolution

selecting the next rule

number of rules to be executed in one cycle
usually one, but several is possible (parallel execution)

order of rules
lowest number,
lowest number after current rule,
lowest numbered rule deriving a new fact, ...

rule complexity e.g. number of premises
most complex (specific) rule first, or most generic (simplest) rule first

order of facts
lowest / highest number,
oldest / newest, ...

in practice combinations of the above criteria are used

Backward Reasoning

goal selection
take one goal and determine all rules capable of satisfying that goal
consequents of the rules must match the goal

matching
check applicable rules; if all premises are satisfied, a rule can be executed, and the goal is solved;
otherwise, new subgoals are created, or the user may provide inputs

usage
unknown response time, possibly many facts, many rules few acceptable conclusions

domains
classification, diagnosis;
inference networks for static knowledge, otherwise pattern matching

Example: Dinner Choices

example backward reasoning

problem
select beverage and main course for a meal

problem analysis

- small number of parameters and rules
- relations known prior to execution
- inputs provided by the user upon request
- planning problem, few possible solutions
- no pattern matching necessary

design decisions

- backward reasoning
- inference network

If all inputs are provided in advance, forward reasoning can be applied

Example: Baseball

example backward reasoning with pattern matching

problem
strategy decisions in a baseball game

problem analysis

- moderate number of parameters and rules
- relations not known prior to execution
- inputs reflect the progress of the game
- decision problem; many possible solutions, but few good ones
- pattern matching necessary

design decisions

- backward reasoning
- pattern matching

in principle, forward reasoning can be applied

Chapter Review

Rule-Based Reasoning with CLIPS

Introduction

Review Lessons "Rule-Based Reasoning", "CLIPS"

Forward Reasoning

Example: Flood Warning Example: Boxer

Rete Algorithm

Example: Cats and Dogs

Backward Reasoning

Example: Dinner Choices Example: Baseball