

```
Loading vc-cvs...
1 package caltool.schedule_ui;
2
3 import caltool.schedule.*;
4 import javax.swing.*;
5 import java.awt.*;
6 import java.awt.event.*;
7
8 *****
9 *
10 * Class DeleteAppointmentButtonListener defines the action listener that
11 * is attached to the OK button in the schedule appointment dialog. When the
12 * class is constructed, it is passed references to the classes that need to be
13 * accessed in the actionPerformed method. In this case, the required classes
14 * are the Schedule model class and the ScheduleAppointmentDialog view class.
15 *
16 * Access to the model is for calling the scheduleAppointment method. Access
17 * to the view is for gathering the data values that are sent to
18 * scheduleAppointment.
19 *
20 */
21
22 public class DeleteAppointmentButtonListener implements ActionListener {
23
24     /**
25      * Construct this with the given Schedule model and parent dialog view.
26      */
27     public DeleteAppointmentButtonListener(Schedule schedule,
28             ScheduleAppointmentDialog dialog) {
29         this.schedule = schedule;
30         this.dialog = dialog;
31     }
32
33     /**
34      * Respond to a press of the OK button by calling ScheduleAppointment with
35      * a new Appointment. The Appointment data are gathered from the
36      * JTextFields and other input fields in the parent dialog.
37      */
38     public void actionPerformed(ActionEvent e) {
39         schedule.deleteAppointment(null);
40     }
41
42     /** The companion model */
43     protected Schedule schedule;
44
45     /** The parent view */
46     protected ScheduleAppointmentDialog dialog;
47
48 }
```