```
Loading vc-cvs...
```

```
  1  package caltool.schedule_ui;
  2
  3  import caltool.schedule.*;
  4  import javax.swing.*;
  5  import java.awt.*;
  6  import java.awt.event.*;
  7
  8  /****
  9   *
 10   * Class ListmeetingTimesButtonListener defines the action listener that is
 11   * attached to the 'List Times' button in the schedule meeting dialog.  The
 12   * actionPerformed method displays a possible meetings times dialog, which in
 13   * turn invokes the Schedule.listPossibleTimes model method.
 14   *
 15   */
 16
 17  public class ListMeetingTimesButtonListener implements ActionListener {
 18
 19      /**
 20       * Construct this with the given Schedule model and parent dialog view.
 21       * Access to the model is for calling its ScheduleAppointment method.
 22       * Access to the parent view is for gathering date to be sent to Schedule.
 23       * ScheduleAppointment.
 24       */
 25      public ListMeetingTimesButtonListener(Schedule schedule,
 26              ScheduleAppointmentDialog dialog) {
 27          this.schedule = schedule;
 28          this.dialog = dialog;
 29      }
 30
 31      /**
 32       * Respond to a press of the OK button by calling ScheduleAppointment with
 33       * a new Appointment.  The Appointment data are gathered from the
 34       * JTextFields and other input fields in the parent dialog.
 35       */
 36      public void actionPerformed(ActionEvent e) {
 37          System.out.println(
 38              "In ListMeetingTimesButtonListener.actionPerformed.");
 39      }
 40
 41      /** The companion model */
 42      protected Schedule schedule;
 43
 44      /** The parent view */
 45      protected ScheduleAppointmentDialog dialog;
 46
 47  }
```