

```
1  /****
2  *
3  * TreeNodeList extends TreeNode by adding a node component and a siblings
4  * component. The node is a reference to a single TreeNode. The siblings
5  * component is a reference to a TreeNodeList, which may contain zero or more
6  * additional TreeNodes. Hence, TreeNodeList is used to represent list
7  * constructs in a parse tree. It can equivalently be viewed as a way to
8  * represent n-ary constructs.
9  *
10 */
11 public class TreeNodeList extends TreeNode {
12
13     /**
14     * Construct this with the given id and child TreeNode references.
15     */
16     public TreeNodeList(TreeNode node, TreeNodeList siblings) {
17         this.node = node;
18         this.siblings = siblings;
19     }
20
21     /**
22     * Return the String representation of this subtree, which is the recursive
23     * toString of each of its nodes, separated by a ';' on a new line plus
24     * another blank line. See the documentation for <a href=
25     * "TreeNode.html#toString()">TreeNode.toString() </a> for a general
26     * description the way trees are represented as strings.
27     */
28     public String toString(int level) {
29         if (siblings == null) {
30             return node == null ? " " : node.toString(level);
31         }
32         else {
33             return (node == null ? " " : node.toString(level)) + "\n;\n\n" +
34                 siblings.toString(level);
35         }
36     }
37
38     /** Reference to the first node of this (sub)list. */
39     TreeNode node;
40
41     /** Reference to the rest of this (sub)list */
42     TreeNodeList siblings;
43
44 }
```