```java
package rolodex;

import javax.swing.*;
import java.awt.*;
import java.awt.event.*;
import java.io.*;
import mvp.*;

/****
 *
 * Class RolodexToolBar is an operational view of the <a href = "Rolodex.html">
 * Rolodex model </a> class.  The RolodexToolBar window is a stand-alone JFrame
 * containing a button for each rolodex operation.  Anonymous instances of
 * JButton are defined for each operation and laid out horizontally in the
 * window.
 *                                                                          <p>
 * RolodexToolBar is exactly the same type of view as the <a href =
 * "RolodexMenu.html"> RolodexMenu view</a>.  As such, RolodexToolBar
 * interfaces with the companion Rolodex model in the same manner as does
 * RolodewxMenu.  The only difference between the two views is in the physical
 * widgets with which the user interacts -- menu items versus push buttons.
 *
 */

public class RolodexToolBar extends View {
    /**
     * Construct this with the given Screen and Rolodex model.
     */
    public RolodexToolBar(Screen s, RolodexMultiViewMenuUI rmui) {

        /*
         * Call the parent constructor.
         */
        super(s, null);

        this.rmui = rmui;

    }

    /**
     * Compose the window of this by adding the horizontal button box.
     */
    public void compose() {

        /*
         * Make the window.
         */
        window = new mvp.Window();


        /*
         * Layout the buttons in a horz box and add the box to the window's
         * content pane.
         */
        Box b = new Box(BoxLayout.X_AXIS);

        JButton ajb = new JButton("Add");
        ajb.addActionListener(
            new ActionListener() {
                public void actionPerformed(ActionEvent e) {
                    rmui.showAddCardDialog();
                }
            }
        );
        ajb.setFont(new Font("Helvetica", Font.PLAIN, 10));
        b.add(ajb);

        JButton djb = new JButton("Delete");
        djb.setFont(new Font("Helvetica", Font.PLAIN, 10));
        djb.addActionListener(
            new ActionListener() {
                public void actionPerformed(ActionEvent e) {
                    rmui.showDeleteCardDialog();
                }
            }
        );
        b.add(djb);

        JButton cjb = new JButton("Change");
        cjb.setFont(new Font("Helvetica", Font.PLAIN, 10));
        cjb.addActionListener(
            new ActionListener() {
                public void actionPerformed(ActionEvent e) {
                    rmui.showChangeCardDialog();
                }
            }
        );
        b.add(cjb);

        JButton fjb = new JButton("Find");
        fjb.setFont(new Font("Helvetica", Font.PLAIN, 10));
        fjb.addActionListener(
            new ActionListener() {
                public void actionPerformed(ActionEvent e) {
                    rmui.showFindCardDialog();
                }
            }
        );
        b.add(fjb);

        window.getContentPane().add(b);

        /*
         * Don't forget to set the title and pack the window.
         */
        window.setTitle("Rolodex Tool Bar");
        window.pack();

    }

    /** The representation of this is a JTextArea. */
    protected JTextArea jta;
```

```

    /** The parent view */
    protected RolodexMultiViewMenuUI rmui;

}
```